

OAM

OAM and product documentation Rampline AS

Innovation and quality since 2008

Rampline AS is a Norwegian company that develops and delivers play and activity equipment for the public environment. Rampline products provides physical development through play and especially stimulates and develop balance and motor skills.

Production and preparation of the products are done at our facility in Talgje, Norway. All our products are in accordance with EN 1176-1:2017.

Mounting instructions are included with all our products.

The importance of maintenance

Damage or malfunction to the play equipment may pose a hazard to the user. Additionally, it will degrade the user experience and the products may be damaged. Therefore, errors should always be corrected. When removing products, always secure the open mounting holes.

Read more about maintenance on www.rampline.no

About the anchoring system

Our play equipment is mounted to concrete foundations with expansion bolts. No movement should be possible at the attachment point. Improper installation, incorrect concrete grade, vandalism or vehicles that collide with the devices can lead to slack at the attachment point.

Spare parts

If vandalism or need for extended maintenance occurs, Rampline AS offers all spare parts throughout the product life. The products are designed with a practical access for replacement of individual parts.

Warranty

See our product warranty description www.rampline.no/product-warranty



OAM and product documentation

RAMPLINE® slackline system

Rampline® slackline system is made for balance play and training.

The ramps are made of hot-dip galvanized and powder-coated steel, padded with 22 mm thick rubber mats.

The tensioning system consists of a stainless steel jack ratchet that is locked with an included code padlock.

The webbing

The webbing is expected to be changed every one or two years, depending on the level of use. A worn webbing does not endanger safety but can result in a degraded user experience. For an optimal user experience, the webbing must always be tight and retightened regularly (tightened 2-3 times during the first 3 weeks, thereafter as needed). Instructions for mounting and adjusting the webbing are included with each webbing, and is also to be found in the product's installation instructions. When buying our slackline devices 3 webbings are included.

You can also watch our instructional video for mounting and tightening the webbing on www.rampline.no

Surface care

Clean with soap and water or rinse gently with high pressure washer. Avoid chemicals that can affect the surface.

The rubber mats on the ramps may over time be affected by light and wear. The rubber surface can be treated with wax. Contact Rampline for guidance.

Should minor damage to the rubber mats occur this can be repaired on site by gluing. Contact Rampline for guidance.

For optimal function of the jack ratchet, lubricate it occasionally with grease spray.

Anchoring

If any slack is detected, this must be rectified by doing the following:

1. In case of a unitary ground cover, such as wet pour rubber: Cut the ground cover over the attachment point
2. Tighten any loose bolts.
3. Glue the cut-out ground cover back in place.

If the device is mounted in loose ground covers (in fall sand, grass or wood chips), just remove the masses that cover the bolts and tighten them.